

CMEX-5 PRO

USB-2 camera with CMOS sensor DC.5000p

HIGHLIGHTS

- Premium camera for education
- Professional version for laboratories and industry
- 5.0 Mpix CMOS color USB 2.0 camera
- 1/2.5" sensor, 2592 x 1944 pixels
- ADC 12 bits, color depth 24 bits
- Low signal/noise ratio
- USB 2.0 interface



CMEX Pro

TECHNICAL SPECIFICATIONS

Sensor	CMOS 1/2.5 inch
Pixels	2592 x 1944 pixels, 5.0 Mpix
Scan mode	Progressive, rolling shutter
Pixel size	2.2 µm x 2.2 µm
Filter	RGB
Mount	C-mount
Max fps	Up to 5 frames per second (2592 x 1944 pixels) Up to 21 frames per second (1280 x 960 pixels) Up to 25 frames per second (1024 x 768 pixels) Up to 38 frames per second (640 x 480 pixels)
ADC	12 bits
Color depth	24 bits
Sensitivity	1.5 V/lux-sec @ 550 nm
Exposure	Automatic or manual, from 1 ms to 800 ms
White balance	Automatic/manual
Dynamic range	65 db
S/N max	45 db
Data interface	USB 2.0 at 480 Mb/s
Operation	0 – 60° C, 45-85 % humidity
Storage temperature	-20 to 70° Celsius
Supplied with	0.45x objective with C-mount, USB 2.0 cable, 30 and 30.5 mm adapters for stereomicroscopes, 76 x 24 mm calibration slide (1mm/100), CD ROM with ImageFocus 4 software, deluxe carrying case
Software	Windows XP, Vista, Windows7, Windows 8 (32 and 64 bit configurations)
Product number	DC.5000p

MODELS

	Number of pixels (MP)	Sensor	Sensor size (inches)	Pixel size (µm)	Resolutions	Max. frames (p/sec)	Grayscale conversion	Color rendering	Signal/ Noise(db)	Dynamic (db)	Sensitivity V/lux-sec	Product number
CMEX-3 Pro	3.2	CMOS	1/2"	3.2 x 3.2	2048x1536	10	12 bits	24 bits	45	72	1.5	DC.3000p
					1024x768	25						
					640x480	40						
CMEX-5 Pro	5.0	CMOS	1/2.5"	2.2 x 2.2	2592 x 1944	5	12 bits	24 bits	45	65	1.5	DC.5000p
					1280 x 960	21						
					1024x 768	25						
					640 x 480	38						

The CMEX Pro cameras are supplied in a deluxe carrying case with USB-2 cable, 30.0 and 30.5 mm to 23.2 mm conversion adapters for use with stereo microscopes, 1mm/100 (10µm/division) calibration slide and a 0.45x C-mount objective