

MULTIPLE STIRRING DRIVES WITH EXTERNAL CONTROL UNIT

Designed for chemical, biotechnical and medical applications of all kinds, developed for maximum requirements, maximum mechanical, thermal and chemical stability as well as uncompromising continuous operation.

MIXdrive 6 / MIXdrive 15 / MIXdrive 60

Ultra-flat, 100% maintenance- and wear-free magnetic stirrer with inductive 2mag-Magnetic-Drive concept for powerful mixing of solutions.

- 🌀 Wear-free magnetic stirrer, up to +200 °C
- 🌀 Submersible, up to +95 °C
- 🌀 Extremely robust construction
- 🌀 Integrable in systems
- 🌀 Developed and made in Germany



Type	MIXdrive 6	MIXdrive 15	MIXdrive 60
Stirring points	6	15	60
Stirring point distance	130 mm	65 mm	32.5 mm
Stirring volume/stirring point	1 - 3.000 ml		1 - 500 ml
Stirring power (max.)	40 W		
Material housing	Stainless steel		
Perm. operation conditions (Basic)	-10 °C up to +50 °C in air, up to +50 °C in water		
Perm. operation conditions (HT)	up to +200 °C in air, up to +95 °C in water		
Operating voltage (max.)	48 VDC		
Dimensions (WxDxH)	245 x 375 x 38 mm		
Protection category	IP68		
Weight (gross) approx.	8.9 kg	9.5 kg	9.7 kg
Order no. Basic-version	40006	40015	40060
Order no. HT-version	40206	40215	40260

Individual units and dimensions on request.
3 years warranty on material and manufacturing.
We reserve the right to make technical alterations. We do not assume liability for errors in printing or typing.

MIXdrive 6

6 stirring positions, suitable for 6 x 1,000 ml Erlenmeyer flasks, stirring point distance 130 mm.

MIXdrive 15

15 stirring positions, suitable for 15 x 250 ml beaker glasses (tall form), stirring point distance 65 mm.

MIXdrive 60

60 (6x10) stirring positions, suitable for 60 testing tubes, ideal for integration, stirring point distance 32,5 mm.

100% synchronized speeds, jerk-free stirring even at low speeds. Fully encapsulated and hermetically sealed stainless steel housing, IP68, water-, dust-, and germproof.

Extremely robust construction and performance, easy to clean and maximum resistance, submersible in water- or oil baths, suitable for the use in CO₂-incubators and ovens.

Two different temperature areas available:

Basic-version up to +50 °C, **HT-version** up to +95 °C submerged in water baths and up to +200 °C in ovens, individual dimensions on request.

Please order control unit separately!

Compatible control units

MIXcontrol eco

MIXcontrol eco DINrail

MIXcontrol 20

MIXcontrol 40

Accessories

ASTEROID 40 - Stirring bar

Stirring bar remover PTFE

Extension cord for MIXdrive

